

KEY INTERLOCKING

A Division of Performance Innovations Ltd.

108 - 7073 Venture Street , Delta,

British Columbia Canada, V4G 1H8

Tel: 604-940-0068

Fax: 604-940-1047

www.keyinterlocking.com

Email: sales@keyinterlocking.com

Account number	PO number	Date Required	Date	Page 1 of

Bill to

Ship to

Purchasing Agents Name

Name	
Phone	
Fax #	

End User

Ordering Guide

A. Lock Type	B. # of Cylinders	C. Plunger length In withdrawn position		D. Bolt Orientation	E. Key Removable Position	F. # of Cylinders “W” for Multiple Cylinders	G. Options	H. Key Interchange
VF -flat mount VB -base mount VD -door mount VN -narrow mount VT -transfer block VC -camlock CM -cylinder mount VP -padlock	1-9 for up to 9 cylinders. Use A for 10 B for 11 C for 12 D for 13 E for 14 F for 15	000 025 037 050 062 075 100 125 137 150 200 300	0” 0mm 1/4” 6.4mm 3/8” 9.5mm 1/2” 12.7mm 5/8” 15.8mm 3/4 19.1mm 1” 25.4mm 1-1/4” 31.7mm 1-3/8” 34.9mm 1-1/2” 38.1mm 2” 50.8mm 3” 76.2mm	L (bolt left) or R (bolt right) EXAMPLE  Bolt Left  Bolt Right	For single cylinder locks, key can be removable “E” (extended) or “W” (withdrawn) For multi cylinder locks “E” (extended) Multi cylinder locks always begin with first cylinder “E”	-Leave blank for single Cylinder locks. -For multiple cylinder locks list the number of “W” (withdrawn) cylinders -Multi cylinder locks always begin with first cylinder “E” Examples of three cylinder locks EEE select 0 for 0 withdrawn EEW select 1 for 1 withdrawn EWW select 2 for 2 withdraw A for 10 , B for 11 etc.	S Switch 1no 1nc SA Snap Action Switch DPDT D Dust cover ADP VD Adapter RP Roll Pin	Examples A1 A2 B1 B2

[illegible]

[illegible]